

# SAFETY DATA SHEET

## Section 1: Identification

 Product Name:
 Technician's Choice TEC584 G-Max Graphene Detail Spray

 Product Code:
 TEC584

 Product Class:
 Exterior Finish Coating

 Manufacturer/Supplier:
 ECP Incorporated

 11210 Katherine's Crossing, Suite 100
 Woodridge, IL 60517

 Telephone:
 630-754-4200

 Emergency Telephone:
 CHEMTREC 800-424-9300

Date Prepared: Date of Review/Update: March 2, 2021

# Section 2: Hazard Identification

Classification of the chemical in accordance with paragraph (d) of §1910.1200:

GHS Hazard Symbols:



GHS Classification: Signal Word:

Skin Corrosion/Irritation Category 3; Eye Damage/Irritation Category 2B Warning

<u>GHS Hazard Statements:</u> H316 Causes mild skin irritation H320 Causes eye irritation

**GHS Precautionary Statements:** 

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P202 Do not handle until all safety precautions have been read and understood.

P264 Wash hands thoroughly after handling.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P332 + P313 If skin irritation occurs: Get medical advice/attention.

P337+ P313 If eye irritation persists: Get medical advice/attention.

#### Signs and Symptoms of Exposure:

 Eye:
 Irritation including tearing or redness.

 Skin:
 Prolonged skin contact may cause irritation including redness, irritation, itching.

 Ingestion:
 May cause gastrointestinal irritation

 Inhalation:
 None are known

 Medical Conditions
 Aggravated by Exposure: None known.

 HMIS Rating:
 Health-1

 Fire-0
 Reactivity-0

 Personal Protection- C

#### Section 3: Composition/Information on Ingredients

Chemical Name	CAS Number	<u>% Range</u>	<u>OSHA PEL</u>	ACGHI TLV
Isopropyl Alcohol	67-63-1	1 - 5	TWA 400ppm	TWA 200ppm
Silicone Micro-Emulsion	Proprietary	1-5	Not Established	Not Established

#### **Section 4: First Aid Measures**

Eye Contact:Flush with large amounts of water for 15 minutes. If symptoms persist, seek medical attention.Skin Contact:Wash affected area with water for 15 minutes. Remove contaminated clothing and launder before reuse.Ingestion:Never give anything by mouth to an unconscious person. If person is conscious then give several glasses of water. Do not induce vomiting. Keep warm and quiet. Seek medical attention.Inhalation:Remove from exposure. Seek fresh air. Keep warm and quiet. If symptoms persist seek medical attention.

# Section 5: Fire-Fighting Measures

Fire and Explosive Properties: Extinguishing Media: Special Fire Fighting Procedures: Unusual Fire and Explosion Hazards:

Flash Point: >140°F / TCC Flammable Limits: LEL / UEL: No Data Water fog, dry chemicals or carbon dioxide. Full protective equipment including self contained breathing apparatus for confined areas. None are known

#### Section 6: Accidental Release Measures

Steps to be taken if Material is Spilled or Leaked:. Contain spill. Ventilate and remove with inert absorbent.

#### Section 7: Handling and Storage

Precautions to be taken in Handling and Storage: Never wear oil soaked clothing. Launder or dry-clean before wearing. Affix proper warning labels on containers in accordance with 29CFR 1010.1200.

#### Section 8: Exposure Controls and Personal Protection

Use only with adequate ventilation. Avoid breathing vapor or mist. Local exhaust preferred. Ventilation: **Respirator Protection:** Properly fitted NIOSH/MSHA approved respirator for ingredients found in SECTION 3 if TLV is exceeded. Gloves rated for protection against ingredients in SECTION 3. Skin Protection: Eye Protection: Safety glasses with side shields or chemical goggles.

# **Section 9: Physical and Chemical Properties**

Boiling Point: 212°F Vapor Density: Unknown Specific Gravity: 1.01 + 0.05% Volatile:  $95.0 \pm 0.5$ Appearance/Odor: White/Black Liquid, Sun Lotion Odor.

### Section 10: Stability and Reactivity

Stability: Stable Hazardous Polymerization: Will not occur. Hazardous Decomposition Products: Various hydrocarbons of incomplete combustion.

#### Section 11: Toxicology Information

IARC, NTP, OSHA Carcinogen:

#### Section 12: Ecological Information

No data

#### Section 13: Disposal Considerations

Waste Disposal: Dispose of in accordance with federal, state, and local regulations.

#### Section 14: Transport Information

D.O.T. REQUIREMENTS (49CFR 172.101): Not regulated by D.O.T.

# Section 15: Regulatory Information

	RQ (REPORTABLE QUAN	TITY) 49CFR 172.1	01: N	lone		
TSCA (Toxic Substances Control Act) Status:		Т	The intentional ingredients of this product are listed.			
	CERCLA RQ - 40CFR 302.	4:	Ν	lone		
	SARA 302 COMPONENTS	- 40CFR 355 Appe	endix A: N	lone		
	SECTION 311/312 HAZAR	D CLASS - 40CFR	<u>370.2</u>			
	Immediate	(X)	R	Reactive	()	
	Delayed	()	S	Sudden Release of Pressure	()	
	Fire	()				
	SARA 313 COMPONENTS	- 40CFR 372.65:	N	lone		
	WORKPLACE HAZARDOL	<b>JS INFORMATION</b>	SYSTEM (WHMIS	<u>S)</u>		
	Ingredient		Max. % By Wt.	<u>LD50</u>		LC50
	Isopropyl Alcohol	67-63-1	1 - 5	5000 mg/kg		45248 ppr
	Silicone Micro-Emulsion		1-5	Not establis	hed	Not establ

**CALIFORNIA PROPOSITION 65:** None

# Section 16: Other Information

Vapor Pressure (mmHg @ 68°F): Unknown Solubility in Water: Complete Melting Point: Not Applicable Not Applicable

Materials to Avoid: Strong oxidizers Conditions to Avoid: Open flames, sources of ignition.

pH:

None

pm blished

Although the information contained herein is believed to be reliable, it is furnished without warranty of any kind. This information is not intended to be all-inclusive as to the manner and conditions of use, handling, and storage.